

Dim	A	B	C	D	E	F	G	H	J
1	66	37	23	36	29	60	68	86	-
2	74	46	25	36	35	59	67	86	-
3	74	46	25	54	35	55	67	86	-
4	74	46	25	58	35	62	82	102	-

1/8" - 1/4" Yanıt Zamanı / Response Time 5 - 30 ms
3/8" - 1" Yanıt Zamanı / Response Time 10 - 35 ms


GEVAX solenoid valfleri tüm ömür ve performans testlerinden geçirilmekte ve tüm ürünler sevki öncesinde %100 çalışma testine tabi tutulmaktadır. Verilen basınç değeri AC gerilimine göre; DC uygulamalarda kullanım özelliklerine göre basınç değeri düşebilir.

Gövde: Paslanmaz Çelik
Kovan: Paslanmaz Çelik
Çekirdek: Paslanmaz Çelik
Yay: Paslanmaz Çelik
Yatak: Paslanmaz Çelik

GEVAX solenoid valves pass through all life-time and performance tests, and all the valves are %100 applied functional tests before delivery.

The pressure values are given for AC coils; for DC applications Pmax may decrease as per applications features.

Body: Stainless Steel
Core Tube: Stainless Steel
Core: Stainless Steel
Springs: Stainless Steel
Seat: Stainless Steel



Normalde Kapalı / Normally Closed

Ölçü (Ports)	Orifice (Ømm)	Kv (l/min)	Fark Basıncı Press. Differential ΔP (bar)		Bobin (Coil)	Dim.	Conta/Diyafram (Seal)	Akışkan Sıcaklığı (Fluid Temp.)	Ağırlık Weight (kg)	Sipariş Kodu (Order Code)
			Pmin	Pmax						
1/8"	2	1,70	0	16	TP1	1	NBR = N	-10 °C+80 °C	0,475	7901-KD...A016-020
1/4"	2	1,70	0	16	TP1	1				0,465
3/8"	3	3,50	0	10	TP4	2	EPDM = E	-10 °C+140 °C	0,465	7901-KD...B010-030
	5	8,00	0	6	TP4	3				0,510
1/2"	6	10,00	0	5	TP4	3	FKM = V	-10 °C+150 °C	0,510	7901-KD...C005-060
	5	8,00	0	6	TP4	3				0,475
3/4"	6	10,00	0	5	TP4	4	PTFE= P	-10 °C+160 °C	0,475	7901-KD...D005-060
1"	6	10,00	0	5	TP4	4				0,800
									0,720	7901-KD...F005-060